

## HVDC Assets Life Cycle Assessment (HVDC - LCA)


**ET Innovation** 


Muhammad Shaban (PhD, CEng) 29/10/2024

nationalgrid


#### Background

NGET and SSEN are jointly developing a subsea HVDC Link between Peterhead in Aberdeenshire and Drax in North Yorkshire.





#### Background





## Why does this matter?

#### To reduce our impact, we first need to understand it

- Clear group and NGET commitments to reduce scope 3 emissions – As a responsible business we need to manage this.
- Assumptions for PC26 and business planning being made using data from onshore AC schemes.
- If we have a good granularity of the schemes carbon footprint, we can focus decarbonisation efforts where the most gains can be made.
- Large pipeline of future HVDC and marine projects in development. Including new technology such as offshore platforms.




#### **Project Overview**

- Funding: Network Innovation Allowance (NIA)
- Partner: DNV Services UK Ltd
- Duration: 06 months

#### Goal

Quantify the carbon baseline of HVDC to get high level understanding for EGL2 project on the environmental impact.

Develop an understanding on main contributors and indicate the highest contributors over HVDC lifetime.



#### **Roadmap to Success**

Base data for HVDC assets, associated equipment (e.g. air cooling and handling) and marine construction equipment (rock armour).



A better methodology for calculating emissions related to the construction of on-site buildings



Updated carbon tools for our supply chain to use that include the detail on HVDC assets and marine work



Roll out updated tools/methodology to existing projects and potential inclusion in HVDC framework



Understand our carbon hotspots and potential workstreams to decarbonise these

Influence the delivery of the 5 offshore link projects


Influence the development of future marine grids (inc platforms) and future offshore link projects

## **Methodology Testing**


The results are based on a representative HVDC setup adjusted to bipolar configuration with 2 stations for an interconnector link.

Converter Stations – 2

Cable – 120 km (100 km subsea)



#### Results



National Grid | [HVDC - LCA] | [20241029]

Transport Waste processing Recycling Disposal or Reuse

Power Losses Repair, replace, refurb Operational energy use SF6 leaks

Converter station & Cables Transport to Site Construction activities



**END OF LIFE** Sustainability, disposal, chemical admixture producers, Recycled products



**OPERATE** Stand-alone operation by relevant owners



START

Construction companies, supply chain, developers, and infrastructure owners


## **Results: Carbon Baseline**



The CO2-eq emissions from one HVDC delivery with two stations and losses over 40 years are **approx. 760,708 tCO2e** during the whole lifetime.




The recycling of materials and equipment could prevent up to **10,160 tCO2e**.



#### Way Forward

**CONVERSION LOSSES** (43.86%) The losses from converting AC to DC and back, are yet the main driver for the environmental impact.



#### **CIVIL AND MATERIAL**

Concrete has the major share of the climate impact from Civil and construction materials.

#### Acknowledgements

#### DNV:

• David Adams, Yongtao Yong

National Grid:

• Jonathan Miller, Alison Fulford, Amal Rose

# nationalgrid